

Electronic Flash

Vivitar[®]
We make it easy™



730AF Flash

*Another Great
Vivitar Product!*

S P E C I F I C A T I O N S

| | |
|--------------------------|--|
| Guide Number | 115 (ISO 100/feet) 35 (ISO 100/meters) at 50mm |
| Auto Flash Range | 2.9-46 feet (0.9-14 meters) at 50mm |
| Auto Thyristor Circuitry | For faster recycle time and greater number of flashes per set of batteries |
| Zoom Flash Head | 28mm, 35mm, 50mm, 85mm |
| Vertical Bounce Flash | 0°-90° |
| Flash Modes | TTL, Auto flash, flash on, manual low and manual high |
| AF Illuminator | 3.3-23 feet/ 1-7 meters (50mm lens) |
| Variable Power | Yes: full, 1/16 |
| Power Source | Uses 4 AA alkaline batteries |
| Dimensions | 7.3 (H) x 2.9 (W) x 1.9 (D) inches (185 x 75 x 50mm) |
| Weight | 7.0 ounces (198 grams) |
| Stock Numbers | Canon AF 231133 Nikon AF 231134 Minolta AF 231136 Pentax 231137 |

Specifications subject to change without notice © 1999 Vivitar Corporation

Features:

- Fully Featured Zoom Flash for Auto Focus SLR Cameras
- Fully featured dedicated flash models for Canon, Nikon and Minolta auto focus SLR cameras.
- Flash head manually zooms to match 28mm, 35mm, 50mm or 85mm focal lengths.
- Vertical bounce flash for softer, more professional quality lighting.
- Swivel flash head - 150° right, 180° left.
- Provides complete TTL auto exposure flash operation
- Automatic operation for easy flash photography.
- Auto Thyristor™ circuitry for faster recycle time and greater number of flashes per set of batteries.

730AF Flash

VIVITAR Corporation
1280 Rancho Conejo Blvd.
Newbury Park, CA 91320
→ (805) 498-7008